# VertiLine83CD
# UL Listed CCTV Rack Mount Power Supply

Rev. DSVertiLine83CD - 12272011

## Overview

VertiLine83CD

Altronix Vertiline83CD CCTV Rack Mount Power Supply provides 8 PTC protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression. Vertiline CCTV Rack Mount Power Supplies are also available in sixteen (16) and twenty-four (24) output models with various power ratings.

## Specifications

### Input:

• 115VAC 60 Hz., 3 amp.

### Output:

- Eight (8) individually selectable 24VAC or 28VAC power outputs with OFF position.
- 24VAC or 28VAC @ 10 amp max. total *(1.25 amp per device, 2.5 amp max.).*
- Eight (8) PTC protected outputs rated @ 2.5 amp.
- Main fuse rated @ 10 amp.
- Surge suppression.

### Electrical:

- Operating temperature: 0º C to 49º C ambient.
- 91-106 BTU/Hr.
- System AC input VA requirement: 345VA.

### Mechanical:

- Units can be rack, wall or shelf mounted.
- Modular 1U standard EIA 19" rack mount chassis
- Enclosure Dimensions (H x W x D approx.): 1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm)
- Product weight (approx.): 9.3 lbs. (4.22 kg.).
- Shipping weight (approx.): 10.6 lbs. (4.81 kg.).

### Features:

- Eight (8) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

## Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-04, Audio, Video and Similar Equipment.

## ***Enclosure Dimensions*** *(H x W x D) (approximate)*:

1.625” (41.275mm) x 19.125” (486mm) x 8.5” (216mm)